

# MATERIAL SAFETY DATA SHEET

## 1. IDENTIFICATION OF THE PRODUCT AND OF THE COMPANY

- 1.1 Identification of the product: **QUICK SHINE P.A. POWER ACTION WOOD FLOOR FINISH**
- 1.2 Use of the product: Water-based polymer finish for sealed hardwood, tile, vinyl, marble, linoleum, no-wax and most other hard surface flooring.
- 1.3 Manufacturer: Holloway House, Inc.  
PO Box 158  
Fortville, IN 46040  
Phone Number: (317) 485-4272
- 1.4 Emergency telephone: Inside United States: (800) 255-3924  
Outside United States: (813) 248-0585
- 1.5 Date of this Material Safety Data Sheet: 04/01/09

## 2. COMPOSITION OF INGREDIENTS

Diethylene Glycol Ethyl Ether (CAS #111-90-0)  
Tributoxyethyl Phosphate (CAS #78-51-3)

## 3. HAZARDS IDENTIFICATION

	Sara III List	OSHA PEL (ppm)	ACGHI TLV(ppm)	Carcinogen Ref. Source*	% By Wt.
Diethylene Glycol Ethyl Ether (CAS #111-90-0)	No	N/E	N/E	(d)	N/A
Tributoxyethyl Phosphate (CAS #78-51-3)	No	NONE	NONE	(d)	N/A

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

\* Chemicals listed as Carcinogen or Potential Carcinogen (a) NTP, (b) ARC Monograph, (c) OSHA, (d) Not Listed, (e) Animal Data Only.

## 4. FIRST AID MEASURES

Skin: Wash exposed skin areas with soap and water. Get medical attention if irritation persists or develops.

## **QUICK SHINE P.A. POWER ACTION WOOD FLOOR FINISH**

Eye: Flush eyes with water for 15 minutes. Get medical attention if irritation develops or persists.

Ingestion: Administer two glasses of water (if victim is conscious). Call physician.

Inhalation: Remove to fresh air. Resuscitate if necessary.

(Most contact is acute rather than chronic)

### **5. FIRE-FIGHTING MEASURES**

Product is non-flammable.

Keep containers cool with water fog.

Unusual Fire and Explosion Hazards. Material can splatter above 100C/212F.

Wear appropriate clothing.

### **6. ACCIDENTAL RELEASE MEASURES**

Follow State and Local Regulations for disposal of large non-reclaimable spills. Keep spectators away. Floor may be slippery. Dike and contain spill. Transfer to containers for recovery or disposal.

Remove contaminate clothing. Launder before reuse. Wash affected skin areas with soap and water. Keep spills out of sewer and open bodies of water.

### **7. HANDLING AND STORAGE**

Keep container closed when not in use.

Keep Out Of Reach of Children

Store at room temperature

Avoid freezing. If frozen, return to room temperature and use in normal manner.

7.1 Handling: See 7 above

7.2 Storage: See 7 above

7.3 This product is specifically designed for use as a floor finish. See directions label on container.

### **8. EXPOSURE CONTROL/PERSONAL PROTECTIONS**

## QUICK SHINE P.A. POWER ACTION WOOD FLOOR FINISH

- 8.1 Exposure limit values. None required in normal use.
- 8.2 Exposures Control:
  - Safety glasses to prevent eye contact. Rubber gloves should be used when handling large amounts of the product.
  - 8.2.1 Occupational exposure controls.
    - None needed in normal use of the product.
    - 8.2.1.1 Respiratory protection.
      - None needed in normal use of the product.
    - 8.2.1.2 Hand protection
      - Rubber gloves recommended when excessive contact is expected.
    - 8.2.1.3 Eye protection
      - Not required in normal use of product.
    - 8.2.1.4 Skin protection
      - Not necessary when using product in normal applications.
  - 8.2.2 Environmental exposure controls.
    - None normally required when product is used as directed.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Milky white liquid

Odor: Acrylic

Important health, safety and environmental information:

PH 8.6 – 8.7

Boiling point: 212 degrees F, Boiling range: N/E

Flash point: non-flammable

Flammability: N/A

Explosive property: N/A

Oxidizing property: N/A

Vapor pressure: (mmHg) 717

Relative density: 8.6 lbs./gl

VOC - 0 grams/liter

### Solubility

Water solubility – dilutable in water

Fat solubility – N/A

Partition

Coefficient: n-octanol/water: N/E

Viscosity: like water

Vapor density: <1

Evaporation rate: <1

(Butyl Acetate)

## QUICK SHINE P.A. POWER ACTION WOOD FLOOR FINISH

### 10. STABILITY AND REACTIVITY

Stable product. Keep container closed when not in use.

10.1 Avoid temperatures above 177C (350F)

10.2 None known

10.3 Hazardous decomposition products: N/E

List hazardous materials produced in dangerous amounts upon decomposition

Need for and the presence of stabilizers: N/A

Possibility of a hazardous exothermic reaction: N/A

Safety significance, if any, of a change in physical appearance of product: N/A

Hazardous decomposition products: N/E

Possibility of degradation to unstable products: N/A

### 11. TOXICOLOGICAL INFORMATION

N/A

### 12. ECOLOGICAL INFORMATION

Ecotoxicity

N/E

Mobility

Known or predicted distribution to environment

Compartments: N/E

Surface tension: N/E

Absorption/desorption: N/E

Persistence and degradability

N/E

Bioaccumulative potential

N/E

Other adverse effects

N/E

### 13. DISPOSAL CONSIDERATIONS

N/E

## QUICK SHINE P.A. POWER ACTION WOOD FLOOR FINISH

### 14. TRANSPORTATION INFORMATION

NA UN Number  
NA class  
NA proper shipping name  
NA packing group  
NA marine pollutant  
NA other applicable information

### 15. REGULATORY INFORMATION

N/A

### 16. OTHER INFORMATION

HEALTH: 1    FLAMMABILITY: 0    REACTIVITY: 0    EQUIPMENT: B

Legend    0 (HMIS) Minimal hazard  
            1 (HMIS) Slight hazard  
            2 (HMIS) Moderate hazard  
            3 (HMIS) Serious hazard  
            4 (HMIS) Severe hazard

We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and of these opinions and the conditions of use of this product are not within the control of Holloway House Inc., it is the user's obligation to determine the conditions of use of this product.